



Product summary

ANN-MB1 antenna

L1/L5 multi-band high precision GNSS antenna

Easy-to-use, reliable multi-band antenna as part of u-blox high precision solution

- L1 /L5 multi-band active GNSS antenna for mass-market applications
- Supports GPS, GLONASS, Galileo, and BeiDou for maximum position availability
- Enables fast time-to-market
- Versatile mounting options to meet diverse installation needs



60.0 x 82.0 x 22.5 mm

Product description

The u-blox ANN-MB1 multi-band (L1/L5/E5a/B2a/NavIC) active GNSS antenna is designed to reduce time-to-market for the new generation of high precision GNSS applications, which require highly accurate location abilities. The compact design, excellent price-to-performance ratio, and versatile mounting choices provide customers with fast, easy, and reliable multi-band antenna solutions. The ANN-MB1 antenna is a perfect match to the u-blox F9 platform (including NEO-F9P-15B, ZED-F9P-15B, and ZED-F9T-10B), supporting L1 and L5 bands, thus providing customers with the valuable antenna solution they need to minimize evaluation and design-in efforts.

Patch antenna characteristics¹

	L1 band	L5/E5a/B2a/NavIC band
Frequency	1559 - 1606 MHz	1164 - 1188 MHz
Impedance	50 Ω	50 Ω
Peak gain	Typ. 3.8 dBic (Zenith)	Typ. 1.3 dBic (Zenith)
Axial ratio	Typ. 3.3 dB (Zenith)	Typ. 3.4 dB (Zenith)
Polarization	RHCP	RHCP

¹ Measured on Ø12 cm ground plane.

Amplifier characteristics

	L1 band	L5/E5a/B2a/NavIC band
Frequency	1559 - 1606 MHz	1164 - 1188 MHz
Gain without cable (at 5 V)	Typ. 29 ± 3.0 dB	Typ. 33 ± 3.0 dB
Noise figure (at 5 V)	Typ. 2.7 dB	Typ. 2.8 dB
Output VSWR	Typ. 2.0	Typ. 2.0
DC voltage	3.0 – 5.0 V	
DC current (at 5 V)	Typ. 15.0 mA	

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.

Copyright © 2023, u-blox AG

UBX-21000238 - R03

Mechanical data

Weight	164 g (typ. including cable)
Size	60.0 x 82.0 x 22.5 mm
Cable	5 m RG174 standard
Connectors (choice)	SMA
Mounting	Magnetic base, fixed installation option
Housing color	Black

Certifications and approvals

CE approval	Based on Radio Equipment Directive (RED) 2014/53/EU and the Restriction of the use of certain Hazardous Substances Directive (RoHS) 2011/65/EU and 2015/863/EU
-------------	--

Environmental data

Operating temperature	-40 °C to +85 °C
Storage temperature	-40° C to +85 °C
Water proof	IP 67

Product variants

ANN-MB1-00	Multi-band (L1/L5) active GNSS antenna, high precision, with 5-meter cable and SMA connector
------------	--

Further information

For contact information, see www.u-blox.com/contact-u-blox.

