


# F9 series Galileo configuration

## Addressing GAL eccentricity

### Application note



### Abstract

This application note explains how to disable Galileo E14 and E18 from being used by the ZED-F9 series receivers. These satellites exhibit eccentric orbits, which might affect u-blox high precision receivers using RTCM3 corrections.

# Document information

Title	<b>F9 series Galileo configuration</b>		
Subtitle	Addressing GAL eccentricity		
Document type	Application note		
Document number	UBX-21000979		
Revision and date	R03	25-Mar-2021	
Disclosure restriction	C1-Public		

## This document applies to the following products:

Product name	Type number	Firmware version	PCN reference
ZED-F9P	ZED-F9P-01B-01	HPG 1.00	N/A
	ZED-F9P-02B-00	HPG 1.10	
		HPG 1.11	
		HPG 1.12	
		HPG 1.13	
ZED-F9H	ZED-F9H-00B-01	HDG 1.12	
	ZED-F9H-01B-00	HDG 1.13	
ZED-F9K	ZED-F9K-01B-01	LAP 1.01	N/A
		LAP 1.20	
ZED-F9R	ZED-F9R-00B-00	HPS 1.00	N/A
	ZED-F9R-01B-00	HPS 1.20	
UBX-F9940-KA-DR	UBX-F9940-KA-C1003A	LAP 1.10	N/A
		LAP 1.20	

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, modification or disclosure to third parties of this document or any part thereof is only permitted with the express written permission of u-blox.

The information contained herein is provided "as is" and u-blox assumes no liability for its use. No warranty, either express or implied, is given, including but not limited to, with respect to the accuracy, correctness, reliability and fitness for a particular purpose of the information. This document may be revised by u-blox at any time without notice. For the most recent documents, visit [www.u-blox.com](http://www.u-blox.com).

Copyright © u-blox AG.

# Contents

<b>Document information</b> .....	<b>2</b>
<b>Contents</b> .....	<b>3</b>
<b>1 Overview of Galileo E14 and E18</b> .....	<b>4</b>
<b>2 Background and symptoms</b> .....	<b>4</b>
2.1 Solution .....	4
<b>3 Setting required configuration</b> .....	<b>5</b>
3.1 List of UBX message options.....	5
<b>Appendix</b> .....	<b>6</b>
<b>A Glossary</b> .....	<b>6</b>
<b>Related documentation</b> .....	<b>7</b>
<b>Revision history</b> .....	<b>7</b>
<b>Contact</b> .....	<b>8</b>

# 1 Overview of Galileo E14 and E18

In 2014 Galileo launched two satellites, E14 and E18, that follow very elliptical orbits, unlike other GNSS satellites which follow almost circular orbits. In comparison to other satellites, the elliptical orbits make the two satellites move differently across the sky.

At the time of writing, these two satellites are marked as unhealthy and as such not used by u-blox receivers.

u-blox recommends applying the configuration instructed in this application note to avoid any problems in the future if the status of the satellites is changed to healthy.

## 2 Background and symptoms

During the time when Galileo E14 and E18 were set healthy, it was noticed that u-blox high precision receivers using RTCM3 corrections were affected.

The typical behavior seen was a degraded position accuracy. The errors were in the order of 2 – 20 cm. The problem could occur during periods when one of the GAL E14/E18 satellites was tracked with a very high elevation angle, when it was one of the highest satellites on the sky. This was typically observed 1 - 3 times per day and could last for up to an hour.

### 2.1 Solution

The current solution is to configure the receiver to not acquire and track these two satellites, E14 and E18, as explained below.

Again, u-blox recommends applying the configuration instructed in this application note to avoid any problems in the future if the status of the satellites is changed to healthy.

In the future, it will be possible to update the receiver firmware to again make full use of these two satellites.

### 3 Setting required configuration

The binary message to disable the use of these two satellites is configured and can be stored in RAM, BBR (battery-backed RAM), and flash.

Writing to RAM will ensure the UBX messages are taken into use immediately. Writing to BBR will allow the UBX message to be carried out at next power on if battery backup is maintained.

Writing to flash will ensure the UBX message will be taken into use at every startup until the firmware is replaced in flash.

The UBX message will be different based on the firmware version the module is running. Check the required UBX message in the tables below:

#### 3.1 List of UBX message options

To store the UBX message to disable the satellites in your selected storage section, send the listed UBX message.

HPG 1.12, HDG 1.12, LAP 1.01, HPS 1.00 and earlier firmware:

Configuration layer	UBX messages
RAM	B5 62 06 8A 1B 00 00 01 00 00 08 00 C6 20 01 09 00 C6 30 FF 02 0B 00 C6 50 00 40 04 00 00 00 00 00 5E
BBRAM	B5 62 06 8A 1B 00 00 02 00 00 08 00 C6 20 01 09 00 C6 30 FF 02 0B 00 C6 50 00 40 04 00 00 00 00 01 78
Flash	B5 62 06 8A 1B 00 00 04 00 00 08 00 C6 20 01 09 00 C6 30 FF 02 0B 00 C6 50 00 40 04 00 00 00 00 00 03 AC

HPG 1.13, HDG 1.13, LAP 1.20, HPS 1.20 firmware:

Configuration layer	UBX messages
RAM	B5 62 06 8A 1B 00 00 01 00 00 08 00 C6 20 01 09 00 C6 30 FF 02 0B 00 C6 50 00 20 02 00 00 00 00 00 DE 72
BBRAM	B5 62 06 8A 1B 00 00 02 00 00 08 00 C6 20 01 09 00 C6 30 FF 02 0B 00 C6 50 00 20 02 00 00 00 00 00 DF 8C
Flash	B5 62 06 8A 1B 00 00 04 00 00 08 00 C6 20 01 09 00 C6 30 FF 02 0B 00 C6 50 00 20 02 00 00 00 00 00 E1 C0

**Table 1: UBX message for selected configuration layer**

- Check that you have received an ACK after the UBX message is sent.
- Refer to the ZED-F9P interface description [1], ZED-F9K interface description [2], ZED-F9R interface description [3], ZED-F9H interface description [5], UBX-F9940-KA-DR interface description [4].

# Appendix


## A Glossary

Abbreviation	Definition
ACK	UBX message received and executed acknowledge
BBR	Battery Backed RAM
eFuse	Electrically Programmable Fuse
Flash	EEPROM (electronically erasable programmable read-only memory)
GAL	Galileo
NOFIX	RTK fixed solution is not achieved
RAM	Random Access Memory
RTK	Real Time Kinematic

**Table 2: Explanation of the abbreviations and terms used**

## Related documentation

- [1] ZED-F9P interface description, [UBX-18010854](#)
- [2] ZED-F9K interface description [UBX-20046191](#)
- [3] ZED-F9R interface description [UBX-19056845](#)
- [4] UBX-F9940-KA-DR interface description [UBX-19028867](#) (NDA)
- [5] ZED-F9H interface description, [UBX-19030118](#)

 For product change notifications and regular updates of u-blox documentation, register on our website, [www.u-blox.com](http://www.u-blox.com).

## Revision history

Revision	Date	Name	Comments
R01	29-01-2021	ghun	Initial release
R02	17-02-2021	mala	Added section Galileo update.
R03	25-03-2021	mala, mstr	Removed section Galileo update and edited chapters 1 and 2.

# Contact

For complete contact information, visit us at [www.u-blox.com](http://www.u-blox.com).

## u-blox Offices

### North, Central and South America

#### u-blox America, Inc.

Phone: +1 703 483 3180  
Email: [info\\_us@u-blox.com](mailto:info_us@u-blox.com)

#### Regional Office West Coast:

Phone: +1 408 573 3640  
Email: [info\\_us@u-blox.com](mailto:info_us@u-blox.com)

#### Technical Support:

Phone: +1 703 483 3185  
Email: [support@u-blox.com](mailto:support@u-blox.com)

### Headquarters

#### Europe, Middle East, Africa

#### u-blox AG

Phone: +41 44 722 74 44  
Email: [info@u-blox.com](mailto:info@u-blox.com)  
Support: [support@u-blox.com](mailto:support@u-blox.com)

### Asia, Australia, Pacific

#### u-blox Singapore Pte. Ltd.

Phone: +65 6734 3811  
Email: [info\\_ap@u-blox.com](mailto:info_ap@u-blox.com)  
Support: [support\\_ap@u-blox.com](mailto:support_ap@u-blox.com)

#### Regional Office Australia:

Phone: +61 3 9566 7255  
Email: [info\\_anz@u-blox.com](mailto:info_anz@u-blox.com)  
Support: [support\\_ap@u-blox.com](mailto:support_ap@u-blox.com)

#### Regional Office China (Beijing):

Phone: +86 10 68 133 545  
Email: [info\\_cn@u-blox.com](mailto:info_cn@u-blox.com)  
Support: [support\\_cn@u-blox.com](mailto:support_cn@u-blox.com)

#### Regional Office China (Chongqing):

Phone: +86 23 6815 1588  
Email: [info\\_cn@u-blox.com](mailto:info_cn@u-blox.com)  
Support: [support\\_cn@u-blox.com](mailto:support_cn@u-blox.com)

#### Regional Office China (Shanghai):

Phone: +86 21 6090 4832  
Email: [info\\_cn@u-blox.com](mailto:info_cn@u-blox.com)  
Support: [support\\_cn@u-blox.com](mailto:support_cn@u-blox.com)

#### Regional Office China (Shenzhen):

Phone: +86 755 8627 1083  
Email: [info\\_cn@u-blox.com](mailto:info_cn@u-blox.com)  
Support: [support\\_cn@u-blox.com](mailto:support_cn@u-blox.com)

#### Regional Office India:

Phone: +91 80 405 092 00  
Email: [info\\_in@u-blox.com](mailto:info_in@u-blox.com)  
Support: [support\\_in@u-blox.com](mailto:support_in@u-blox.com)

#### Regional Office Japan (Osaka):

Phone: +81 6 6941 3660  
Email: [info\\_jp@u-blox.com](mailto:info_jp@u-blox.com)  
Support: [support\\_jp@u-blox.com](mailto:support_jp@u-blox.com)

#### Regional Office Japan (Tokyo):

Phone: +81 3 5775 3850  
Email: [info\\_jp@u-blox.com](mailto:info_jp@u-blox.com)  
Support: [support\\_jp@u-blox.com](mailto:support_jp@u-blox.com)

#### Regional Office Korea:

Phone: +82 2 542 0861  
Email: [info\\_kr@u-blox.com](mailto:info_kr@u-blox.com)  
Support: [support\\_kr@u-blox.com](mailto:support_kr@u-blox.com)

#### Regional Office Taiwan:

Phone: +886 2 2657 1090  
Email: [info\\_tw@u-blox.com](mailto:info_tw@u-blox.com)  
Support: [support\\_tw@u-blox.com](mailto:support_tw@u-blox.com)