



Product Summary

MAX-8 series

Small u-blox 8 GPS modules

Small GPS modules for easy manufacturing

- High sensitivity of -166 dBm for single GNSS reception
- Cost-efficient system
- TCXO-based variant for fastest time to first fix
- Low power consumption
- Superior anti-spoofing and anti-jamming
- Pin-compatible to MAX-7



9.7 × 10.1 × 2.5 mm



Product description

The MAX-8 series of standard precision GNSS modules features the reliable performance of the u-blox 8 positioning engine, which receives GPS, GLONASS, QZSS and SBAS signals. The MAX-8 series delivers high sensitivity and minimal acquisition times in the ultra compact MAX form factor.

The economical MAX-8 series provides high sensitivity while featuring low power consumption and supporting advanced Power Save Modes. It also provides message integrity protection, geofencing, spoofing detection, and odometer functionalities.

The MAX-8C is optimized for cost sensitive applications with lowest power, while the MAX-8Q provides best performance. The industry proven MAX form factor allows easy migration from MAX-7 and MAX-6 modules by offering backward compatibility. Sophisticated RF-architecture and interference suppression ensure maximum performance even in GNSS-hostile environments. The MAX-8 series combines a high level of integration capability with flexible connectivity options in a miniature package. This makes it perfectly suited for industrial and mass-market end products with strict size and cost requirements. The DDC (I²C compliant) interface provides connectivity and enables synergies with most u-blox cellular modules.

u-blox 8 modules use GNSS chips qualified according to AEC-Q100 and are manufactured in ISO/TS 16949 certified sites. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment". MAX-8Q complies with green/halogen free standards.

	MAX-8C	MAX-8Q
Grade		
Automotive		
Professional	•	•
Standard		
GNSS		
GPS / QZSS	•	•
GLONASS	•	•
Galileo		
BeiDou		
Number of concurrent GNSS	1	1
Interfaces		
UART	1	1
USB		
SPI		
DDC (I ² C compliant)	1	1
Features		
Oscillator	C	T
RTC crystal	◆	•
Timepulse	1	1
Power supply		
1.65 V – 3.6 V	•	
2.7 V – 3.6 V		•

◆ = Yes, but with higher backup current

C = Crystal / T = TCXO



MAX-8 series

Features

Receiver type	72-channel u-blox 8 engine GPS/QZSS L1 C/A, GLONASS L1 FDMA, SBAS: WAAS, EGNOS, MSAS	
Nav. update rate	Up to 18 Hz	
Position accuracy	GPS	GLONASS
Autonomous	2.5 m CEP	4.0 m CEP
Acquisition ¹		
Cold starts:	29 s	30 s
Aided starts:	2 s	2 s
Reacquisition:	1 s	1 s
Sensitivity ¹		
Tracking:	-166 dBm	-166 dBm
Cold starts:	-148 dBm	-145 dBm
Hot starts:	-157 dBm	-156 dBm
Assistance GNSS	AssistNow Online AssistNow Offline (up to 35 days) AssistNow Autonomous (GPS only, up to 3 days) OMA SUPL & 3GPP compliant	
Oscillator	TCXO (MAX-8Q) Crystal (MAX-8C)	
RTC crystal	Built-in (MAX-8Q) Cost efficient solution with higher backup current (MAX-8C)	
Anti jamming	Active CW detection and removal	
Memory	Onboard ROM	
Supported antennas	Active and passive	
Raw data	Code phase output	
Odometer	Integrated in navigation filter	
Geofencing	Up to 4 circular areas GPIO for waking up external CPU	
Spoofing detection	Built-in	
Signal integrity	Signature feature with SHA 256	

1 MAX-8Q

Electrical data

Power supply	1.65 V to 3.6 V (MAX-8C) 2.7 V to 3.6 V (MAX-8Q)
Digital I/O voltage level	1.65 V to 3.6 V (MAX-8C) 2.7 V to 3.6 V (MAX-8Q)
Power Consumption ²	16 mA @ 3 V (Continuous) 3.8 mA @ 3 V Power Save mode (1 Hz)
Backup Supply	1.4 V to 3.6 V

2 MAX-8C, default mode: GPS incl. QZSS, SBAS

Package

18 pin LCC (Leadless Chip Carrier): 9.7 x 10.1 x 2.5 mm, 0.6 g

Environmental data, quality & reliability

Operating temp.	-40 °C to +85 °C
Storage temp.	-40 °C to +85 °C
RoHS compliant (lead-free)	
Green (halogen-free): MAX-8Q	
Qualification according to ISO 16750	
Manufactured in ISO/TS 16949 certified production sites	
Uses u-blox 8 chips qualified according to AEC-Q100	

Interfaces

Serial interfaces	1 UART 1 DDC (I ² C compliant)
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Timepulse	Configurable: 0.25 Hz to 10 MHz
Protocols	NMEA, UBX binary, RTCM

Support products

u-blox 8 Evaluation Kits:

Easy-to-use kits to get familiar with u-blox 8 positioning technology, evaluate functionality, and visualize GNSS performance.

EVK-8N	u-blox 8 GNSS Evaluation Kit, with TCXO, supports MAX-8Q
EVK-M8C	u-blox M8 GNSS Evaluation Kit (in single GPS or single GLONASS mode), with Crystal, supports MAX-8C

Product variants

MAX-8C	u-blox 8 GNSS LCC module, crystal, ROM
MAX-8Q	u-blox 8 GNSS LCC module, TCXO, ROM

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the [product data sheet](#).

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2021, u-blox AG