

UBX-G8020-KT




u-blox 8 GPS chip

Cost-efficient low power GPS chip

- GNSS engine for GPS/QZSS and GLONASS
- High sensitivity of -166 dBm
- Low power consumption
- Advanced jamming and spoofing detection
- Superior performance for wrist worn devices
- Pin-compatible with UBX-G7020-KT and UBX-M8030-KT



5.00 × 5.00 × 0.59 mm



Product description

The UBX-G8020-KT GNSS chip, based on the latest u-blox 8 position engine, supports GPS/QZSS, GLONASS, and SBAS. With superior sensitivity and acquisition times, it sets new standards for single constellation receivers.

UBX-G8020-KT chip is targeted for applications where small size, high performance, minimal power, and low system costs are all a must. With a dedicated mode for wrist worn applications, UBX-G8020-KT is a perfect choice for wearable devices. UBX-G8020-KT features low power consumption and supports advanced Power Save Modes. It also provides message integrity protection, geofencing, spoofing detection, odometer, and data logging functionalities.

The UBX-G8020-KT is available in an industry standard QFN package. Featuring built-in LNA, LDOs and DC/DC converter, and a small external BOM, the UBX-G8020-KT enables ultra-small solutions with a footprint of only ~50 mm². By supporting TCXOs or lower price oscillators, the UBX-G8020-KT further ensures a minimal Total-Cost-of-Ownership.

UBX-G8020-KT was built with backward compatibility in mind, thus simplifying migration from existing u-blox G7020-KT designs.

With its rigorous quality and manufacturing standards (AEC-Q100, ISO/TS 16949), UBX-G8020-KT meets the requirements for industrial and consumer applications.

UBX-G8020-KT

Grade	
Automotive	
Professional	•
Standard	
GNSS	
GPS / QZSS	•
GLONASS	•
Galileo	
BeiDou	
Number of concurrent GNSS	1
Interfaces	
UART	1
USB	1
SPI	1
DDC (I ² C compliant)	1
Features	
Data logging	S
RTC crystal	S
Oscillator	C/T
Antenna supply & supervisor	S
Timepulse	2

S = supported, may require ext. components C/T = Crystal and TCXO supported



Features

Receiver type	72-channel u-blox 8 engine GPS/QZSS L1 C/A, GLONASS L10F SBAS L1 C/A: WAAS, EGNOS, MSAS	
Time to first fix ¹	GPS	GLONASS
Cold starts:	29 s	30 s
Aided start:	2 s	2 s
Hot start:	1 s	1 s
Sensitivity ¹		
Tracking & Nav:	-166 dBm	-166 dBm
Reacquisition:	-160 dBm	-156 dBm
Cold start:	-148 dBm	-145 dBm
Hot start:	-157 dBm	-156 dBm
Max nav. update rate	Up to 18 Hz	
Horizontal Pos. Accuracy	GPS 2.5 m CEP	GLONASS 4.0 m CEP
Multi-GNSS Assistance	AssistNow GNSS Online AssistNow GNSS Offline (up to 35 days) AssistNow Autonomous (up to 6 days)	
Oscillator	Supports Crystal or TCXO	
LNA	Built-in	
RTC input	32.768 kHz (optional), RTC can be derived from GNSS Crystal	
Antenna supervision	Short and open circuit detection supported with external circuit	
DC/DC converter	Built-in, external component required	
Anti Jamming	Active CW detection and removal	
Raw Data	Code phase output	
Odometer	Integrated in navigation filter	
Geofencing	Up to 4 circular areas; GPIO for waking up external CPU	
Spoofing detection	Built-in	
Signal integrity	Signature feature with SHA 256	
Data logging ²	For position, velocity, time, and odometer data	

1 = with TCXO

2 = External Flash required

Package

UBX-G8020-KT: 40 Pin QFN: 5.00 x 5.00 x 0.59 mm

Environmental data, quality & reliability

Operating temp.	-40 °C to +85 °C
Storage temp.	-40 °C to +125 °C
Humidity	JEDEC MSL 1
RoHS compliant (lead-free) and green (no halogens)	
Qualification according to AEC-Q100	
Manufactured in ISO/TS 16949 certified production sites	

Electrical data

Supply voltage	1.4 V to 3.6 V
Digital I/O voltage level	1.65 V to 3.6 V
Power consumption	16 mA @ 3.0 V (continuous mode) 3.7 mA @ 3.0 V (PSM, 1 Hz update)
Backup Supply	1.4 V to 3.6 V

Interfaces

Serial interfaces	1 UART 1 USB V2.0 compatible 1 DDC (I ² C compliant) 1 SPI
Digital I/O	2 configurable time pulses 2 EXTINT interrupt inputs 2 PIO for antenna supervision

Support products

Easy-to-use kits to get familiar with u-blox 8 positioning technology, evaluate functionality, and visualize GNSS performance.

EVK-8N	u-blox 8 GNSS Evaluation Kit with TCXO
--------	----------------------------------------

Product variants

UBX-G8020-KT	u-blox 8 GNSS chip, 40 pin QFN
--------------	--------------------------------

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the [product data sheet](#).

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2018, u-blox AG