

# ZED-F9T series

## u-blox F9 high accuracy timing modules

### Multi-band GNSS receiver with nanosecond-level timing accuracy

- Meets the most stringent 5G timing requirements
- Ideal for global deployments due to GPS, BeiDou, Galileo, and NavIC reception
- Unaffected by ionospheric errors
- Differential timing mode for highly accurate local timing
- Built-in security, including Galileo OSNMA, for highest robustness against malicious attacks



Standard




Professional



Automotive

17.0 × 22.0 × 2.4 mm



### Product description

ZED-F9T timing modules provide nanosecond-level timing accuracy to the most demanding infrastructure applications. ZED-F9T is designed to meet the most stringent timing synchronization requirements in 5G mobile networks on a global scale. By significantly reducing the time error of the primary source of cellular network synchronization, the ZED-F9T module will help operators maximize the performance of their networks and so optimize the return on their investment in 5G communications.

The module's multi-band capability reduces the timing error under clear skies to less than 5 ns without the need of an external GNSS correction service. To further improve accuracy locally, the ZED-F9T features a differential timing mode, which exchanges correction data with other neighboring GNSS timing receivers via a communication network.

Multi-band access to all four global satellite constellations strengthens the receiver's capability for delivering more reliable performance. To maximize GNSS signal support and design flexibility, the ZED-F9T module is available as three pin-compatible band versions, supporting L1/L2/E5b and L1/L5/E5a configurations.

ZED-F9T includes advanced security features such as secure boot, secure interfaces, Galileo OSNMA, and T-RAIM to provide the highest level timing integrity.

The module has a single RF input for all the GNSS bands and dual SAW filters for exceptional signal selectivity and out-of-band attenuation.

u-blox modules use GNSS chips qualified according to AEC-Q100, are manufactured in ISO/TS 16949 certified sites, and are fully tested on a system level. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment".

	ZED-F9T-00B	ZED-F9T-10B	ZED-F9T-20B
<b>Grade</b>			
Automotive			
Professional	•	•	•
Standard			
<b>GNSS</b>			
GPS / QZSS	•	•	•
GLONASS	•	•	
Galileo	•	•	•
BeiDou	•	•	•
NavIC		•	•
Multi-band	L1/L2/E5b	L1/L5/E5a	L1/L2/E5b and L1/L5/E5a
<b>Interfaces</b>			
UART	2	2	2
USB	1	1	1
SPI	1	1	1
DDC (I2C compliant)	1	1	1
<b>Features</b>			
Programmable (Flash)	•	•	•
Galileo OSNMA			•
Carrier phase output	•	•	•
Additional SAW	•	•	•
RTC crystal	•	•	•
Oscillator	T	T	T
Survey-in and fixed mode	•	•	•
Time pulse output	2	2	2
Time mark input	2	2	2
<b>Power supply</b>			
2.7 V – 3.6 V	•	•	•

T = TCXO

# ZED-F9T module



## Features

Receiver type	184-channel u-blox F9 engine	
	ZED-F9T-00B:	
	GPS L1C/A, L2C	QZSS L1C/A, L2C
	GAL E1B/C, E5b	BDS B1I, B1C, B2I
	GLO L1OF, L2OF	
	SBAS L1C/A: WAAS, EGNOS, MSAS, GAGAN	
	ZED-F9T-10B:	
	GPS L1C/A, L5	QZSS L1C/A, L5
	GAL E1B/C, E5a	BDS B1I, B1C, B2a
	NavIC L5	GLO L1OF
	SBAS L1C/A: WAAS, EGNOS, MSAS, GAGAN	
	ZED-F9T-20B:	
	GPS L1C/A, L2C, L5	QZSS L1C/A, L2C, L5
	GAL E1B/C, E5b, E5a	BDS B1I, B1C, B2a, B2I
	NavIC L5	
	SBAS L1C/A: WAAS, EGNOS, MSAS, GAGAN	
Nav. update rate <sup>1</sup>	up to 20 Hz	
Position accuracy <sup>2</sup>	Standalone	1.5 m CEP
Acquisition	Cold starts	26 s
	Aided starts	2 s
	Reacquisition	1 s
Sensitivity	Tracking and Nav.	-167 dBm
	Reacquisition	-160 dBm
	Hot starts	-157 dBm
	Cold starts	-148 dBm
Assistance	AssistNow Online OMA SUPL and 3GPP compliant	
Oscillator	TCXO	
RTC crystal	Built-in	
Anti-jamming	Active CW detection and removal Dual onboard band pass filters	
Anti-spoofing	Advanced anti-spoofing algorithms Galileo OSNMA	
Security	Secure boot Secure firmware update	
Memory	Flash	
Supported antennas	Active	

## Features - Timing

Timing accuracy	<5 ns (1-sigma, clear sky, absolute mode) <2.5 ns (1-sigma, clear sky, differential mode)
Time pulse frequency	0.25Hz – 25 MHz
Time pulse jitter	±4 ns
Time mark resolution	8 ns
Integrity reports	T-RAIM active, phase uncertainty Time pulse rate/duty-cycle, inter-constellation biases
Survey-in period	Configurable

## Features - Raw data

Measurement data	Carrier phase, code phase and pseudo-range, Doppler on all signals
Message data	GPS, BeiDou, Galileo, GLONASS, NavIC, QZSS, SBAS

## Further information

For contact information, see [www.u-blox.com/contact-u-blox](http://www.u-blox.com/contact-u-blox).  
For more product details and ordering information, see the product data sheet.

## Package

54-pin LGA (Land Grid Array)  
17.0 x 22.0 x 2.4 mm

## Environmental data, quality and reliability

Operating temp.	-40 °C to +85 °C
Storage temp.	-40 °C to +85 °C
RoHS compliant (lead-free)	
ETSI-RED compliant	
Qualification according to ISO 16750	
Manufactured and fully tested in ISO/TS 16949 certified production sites	
Uses u-blox F9 chips qualified according to AEC-Q100	
High vibration and shock resistance	

## Electrical data

Supply voltage	2.7 V to 3.6 V
Power consumption	68 mA @ 3.0 V (continuous)
Backup supply	1.65 V to 3.6 V

## Interfaces

Serial interfaces	1 USB
	2 UART
	1 SPI
	1 DDC (I2C compliant)
Protocols	NMEA, UBX binary, RTCM version 3.3
Time pulse output	2
Time mark input	2

## Support products

u-blox support products provide reference design, and allow efficient integration and evaluation of u-blox positioning technology.

M2-ZED-F9T	u-blox F9 multi-band GNSS timing card
RCB-F9T	u-blox F9 multi-band GNSS timing board
EVK-F9T	u-blox F9 GNSS timing evaluation kit
ANN-MB2	All-band high precision GNSS antenna

## Product variants

ZED-F9T-00B	u-blox F9 high accuracy timing module, with L1/L2/E5b bands
ZED-F9T-10B	u-blox F9 high accuracy timing module, with L1/L5/E5a bands
ZED-F9T-20B	u-blox F9 high accuracy timing module, with L1/L2/E5b and L1/L5/E5a bands

- 1 The highest navigation rate can limit the number of supported constellations
- 2 Depends on atmospheric conditions, GNSS antenna, multipath conditions, satellite visibility, and geometry

## Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos, and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose, or content of this document. This document may be revised by u-blox at any time. For most recent documents and product statuses, please visit [www.u-blox.com](http://www.u-blox.com).

Copyright © 2025, u-blox AG