

NORA-W10 series



Stand-alone multiradio modules

Powerful wireless MCU with enhanced security

- Wi-Fi 4 (802.11b/g/n) and Bluetooth Low Energy v5.0
- Powerful open CPU for advanced customer applications
- Small footprint and multiple antenna options with superior RF performance
- AI support for speech and face recognition
- Enhanced security features
- Global certification



10.4 × 14.3 × 1.8 mm



NORA-W101-00B
NORA-W106-00B
NORA-W106-10B

Product description

The NORA-W1 series of stand-alone multiradio modules integrate a powerful 32-bit, dual core microcontroller unit (MCU) and a radio for wireless communication. The radio provides support for 802.11b/g/n Wi-Fi in the 2.4 GHz ISM band and Bluetooth Low Energy (LE) v5.0 communications. The Bluetooth LE subsystem supports advertisement extensions and long range through coded PHY.

The modules come in a host-less, open CPU configuration that allows customer applications to run on the module itself – without any need for a supporting host MCU.

NORA-W10 offers a wireless MCU, flash memory, crystal, and antenna – together with all of the other components required for matching, filtering, and decoupling – in a compact stand-alone multiradio module. It also supports a wide range of IO interfaces, such as GPIO, UART, USB OTG, SPI, I2S, I2C, PWM, RMT, CAN and SD/MMC host.

The modules can be used to design solutions with top-grade security, thanks to integrated cryptographic hardware accelerators, RSA-based secure boot, digital signature, flash encryption, HMAC, and support for running a fully trusted execution environment.

With integral support for neural network inference on the MCU using accelerated vector instructions, NORA-W10 is an ideal candidate for voice- and face-recognition applications.

Device design is simplified, as developers can choose to use an external antenna (NORA-W101) or take advantage of the internal antenna (NORA-W106). Pin-compatible with all other NORA modules, NORA-W10 also provides maximum flexibility for the development of similar devices offering different radio technologies.

As NORA-W10 modules are globally pre-certified, less time is needed for test and validation, thus reducing product time to market. The professional grade modules support an extended temperature range of –40 °C to +85 °C. They are qualified according to u-blox Qualification Policy, based on AEC-Q104.

	NORA-W101-00B	NORA-W106-00B	NORA-W106-10B
Grade			
Automotive			
Professional	•	•	•
Standard			
Radio			
Chip inside	ESP32-S3	ESP32-S3	ESP32-S3
Bluetooth qualification	v5.0	v5.0	v5.0
Bluetooth low energy	•	•	•
Bluetooth output power EIRP [dBm]	10	10	10
Antenna type (see footnotes)	pin	pcb	pcb
Wi-Fi 2.4 / 5 [GHz]	2.4	2.4	2.4
Wi-Fi IEEE 802.11 standards	b/g/n	b/g/n	b/g/n
Wi-Fi output power EIRP [dBm]	20	20	20
Max Wi-Fi range [meters]	500	500	500
Application software			
Open CPU for embedded applications	•	•	•
Interfaces			
USB OTG	◆	◆	◆
UART - 3x	◆	◆	◆
SPI - 4x	◆	◆	◆
I2C - 2x	◆	◆	◆
I2S - 2x	◆	◆	◆
TWAI® (CAN specification 2.0)	◆	◆	◆
SDIO host controller	◆	◆	◆
DVP camera interface	◆	◆	◆
LCD	◆	◆	◆
PWM	◆	◆	◆
GPIO pins (user available)	38	38	33
AD converters [number of bits]	12	12	12
Features			
AI acceleration [bits]	8/16	8/16	8/16
Bluetooth mesh	◆	◆	◆
Wi-Fi and Bluetooth co-existence	◆	◆	◆
MCU (see footnotes)	LX7	LX7	LX7
RAM [kB]	512	512	8192
Flash [MB]	8	8	ext
Max Wi-Fi data rate [Mbit/s]	150	150	150
Secure boot	◆	◆	◆
Flash encryption	◆	◆	◆
Isolated execution environment support	◆	◆	◆
Cryptographic hardware acceleration	◆	◆	◆
OTP	◆	◆	◆

pin = Antenna pin
pcb = Internal PCB antenna
ext = External flash required

LX7 = 240 MHz dual-core Xtensa LX7
◆ = Feature enabled by HW. Support depends on the open CPU app SW.

NORA-W10 series



Features

Wi-Fi standards	802.11b/g/n
Wi-Fi channels	2.4 GHz channels 1-13
Wi-Fi maximum transfer rates	802.11b: 11 Mbit/s 802.11g: 54 Mbit/s 802.11n: 72 Mbit/s (Max, HT20) 150 Mbit/s (Max, HT40)
Output power	Wi-Fi: 20 dBm EIRP Bluetooth low energy: 10 dBm EIRP
Sensitivity (conducted)	Wi-Fi: -97 dBm Bluetooth low energy: -98 dBm
Bluetooth	v5.0 Bluetooth Low Energy
Antenna	Internal antenna or antenna pin for connecting to the external antenna

Electrical data

Power supply	3.0 V to 3.6 V
Power consumption	Wi-Fi Tx 802.11n HT20 16.5 dBm: 286 mA (100% duty cycle) Bluetooth Low Energy 0 dBm: 220 mA (100% duty cycle) Light-sleep mode: 240 µA Deep-sleep mode: 7 µA

Interfaces

All variants	UART USB OTG SPI I2C I2S JTAG TWAI (CAN 2.0 specification) SDIO host DVP LCD PWM GPIO ADC
--------------	---

Package

Dimensions	10.4 x 14.3 x 1.8 mm
Weight	< 1 g
Mounting	Machine mountable Solder pins

Environmental data, quality & reliability

Operating temperature	-40 °C to +85 °C
Storage temperature	-40 °C to +85 °C
Humidity	RH 5-90% non-condensing

Certifications and approvals

Type approvals	Europe (ETSI RED), United Kingdom (UKCA), US (FCC/CFR 47 part 15 unlicensed modular transmitter approval), Canada (IC RSS), Japan (MIC), Taiwan (NCC) ¹ , South Korea (KCC), Australia (ACMA), New Zealand, Brazil (Anatel) ¹ , South Africa (ICASA) ¹
Health and safety	EN 62479, EN 62368-1, IEC 62311
Medical Electrical Equipment	IEC 60601-1-2
Bluetooth qualification	v5.0

¹ = Certifications are pending

Support products

EVK-NORA-W101	Evaluation kit for NORA-W101-00B module with antenna pin
EVK-NORA-W106	Evaluation kit for NORA-W106-00B module with internal PCB antenna
USB-NORA-W106	Evaluation kit for NORA-W106-00B module with internal PCB antenna; USB-stick format

Product variants

NORA-W101-00B	Multiradio wireless MCU module with antenna pin
NORA-W106-00B	Multiradio wireless MCU module with internal PCB antenna
NORA-W106-10B	Multiradio wireless MCU module with internal PCB antenna and 8 MB RAM

Further information

For contact information, see www.u-blox.com/contact-u-blox.

For more product details and ordering information, see the product data sheet.

Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose, or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.