


# SARA-S520BM10 module



## LTE-M / ORBCOMM satellite / GNSS module with u-blox chipset

Based on u-blox UBX-S52 chipset for multimode connectivity with satellites and cellular networks

- First u-blox cellular module compliant with ORBCOMM IDP protocol
- Multimode module: cellular and satellite connectivity with GNSS positioning
- Product longevity and best support guaranteed by u-blox LTE and GNSS chipsets
- u-blox M10 GNSS receiver delivers accurate and reliable positioning, concurrently with LTE
- Smallest multimode IoT module at ~400 mm<sup>2</sup> in the SARA form factor



### Product description

The SARA-S520BM10 module, powered by the u-blox UBX-S52 cellular chipset and the u-blox M10 GNSS receiver chip, offers comprehensive connectivity capabilities, including access to satellite connectivity. It relies on ORBCOMM network access via the IDP protocol. With complete hardware and software ownership, u-blox ensures long-term device availability and lifetime support at the chipset level.

Designed for applications requiring constant network connectivity worldwide, the module leverages the GEO satellite network ecosystem to ensure seamless coverage across the globe. Support of the ORBCOMM networks enables customers to use SARA-S520BM10 everywhere in the world, making devices using this module truly global.

IDP is fully reliable protocol designed for IoT solutions that need to transmit data from everywhere in the world.

On top of the satellite connectivity, this module supports LTE Cat M1 optimized for IoT applications. It boasts enhancements in power consumption, coverage, data rate, and mobility.

The SARA-S520BM10 integrates the u-blox M10 GNSS receiver to deliver best-in-class positioning data concurrent with the LTE communication, making it the ideal solution for continuous or cyclic tracking applications.

Grade	
Automotive	
Professional	•
Standard	
Regions	
	Global
Access technology	
LTE bands	1, 2, 3, 4, 5, 8, 12, 13, 18, 19, 20, 25, 26, 28, 66, 71, 85
Data rate	M1
LTE power class	23 dBm
Satellite protocol	IDP
Satellite bands	L-band
Satellite power class	33 dBm
Positioning	
Integrated GNSS receiver	•
Dedicated GNSS antenna interface	•
Compatible u-blox services	
AssistNow™	•
CellLocate®	•
CloudLocate	•
Interfaces	
UART	2
USB (for diagnostics)	1
DDC (I2C)	1
USIM	1
GPIO	6
Features	
Ultra low PSM	•
Secure boot and updates	•
HTTP, FTP	•
TCP/UDP	•
TLS/DTLS	•
CoAP	•
LwM2M	•
uFOTA	•
FW update via serial (FOAT)	•
Last gasp	•
Jamming detection	•
CellTime	•

M1 = LTE Cat M1 (588 kb/s DL, 1200 kb/s UL)

# SARA-S520BM10 module



## Features

LTE	<b>3GPP Releases:</b> 13, 14 with partial support for LTE Cat M1 Cat M1 Half-duplex, 588 kb/s DL, 1200 kb/s UL
SAT	IDP protocol Latency less than 15 sec for 100 bytes less than 60 sec for 1000 bytes Maximum payload: 6.4 kbytes UL 10.0 kbytes DL
SMS	MT/MO PDU / text mode SMS over SG/NAS

## Compatible u-blox services

Location	AssistNow™ CellLocate® CloudLocate
----------	--

## Software features

Protocols	Dual stack IPv4 and IPv6 PPP over IPv4 and IPv6 Embedded TCP/IP, UDP/IP, FTP, HTTP, DNS Embedded MQTT and MQTT-SN Embedded CoAP and LwM2M Embedded TLS/DTLS SIM provisioning (BIP)
Positioning	GNSS antenna interface shared with satellite Integrated u-blox M10 chip with concurrent GNSS (GPS, GLONASS, BeiDou, Galileo)
Functionalities	CellTime for robust and accurate timing reference Last gasp Jamming detection Antenna and SIM detection
Firmware upgrade	Cellular: Via UART uFOTA client/server solution (firmware upgrade over the air) Satellite: OTA via satellite connection

## Interfaces

Serial	8-wire UART, configurable as 2x 4-wire UART with ring indication DDC (I2C) USB for diagnostics
GPIO	Up to 6 GPIOs, configurable
(U)SIM	Supports 1.8 V and 3.0 V

### Note:

SARA-S520BM10 was initially named SARA-S520M10L.

## Package

96 pin LGA: 16.0 x 26.0 x 2.4 mm, < 3 g

## Environmental data, quality & reliability

Operating temperature	-40 °C to +85 °C
RoHS compliant (lead-free)	
Qualification according to AEC-Q104	
Manufactured in ISO/TS 16949 certified production sites	

## Certifications and approvals

SARA-S520BM10 <sup>1</sup>	FCC, ISED, GCF, PTCRB, RED, RCM, NCC, Verizon, AT&T with FirstNet, T-Mobile, Telus, Deutsche Telekom, Telstra, Orange
SARA-S520BM10	AWS IoT Core qualified Microsoft Azure certified

1 = Planned certifications

## Electrical data

Power supply	3.8 V nominal, range 3.0 V to 4.5 V
PSM current consumption	1 µA
eDRX current consumption	180 µA
LTE Cat M1 Connected mode current consumption	195 mA (at 23 dBm)
Satellite Connected mode current consumption	TBD

## Support products

EVK-SARA-S520BM10	Evaluation kit for SARA-S520BM10
-------------------	----------------------------------

## Product variants

SARA-S520BM10	LTE-M and satellite module with integrated u-blox M10 GNSS receiver for global use
---------------	--

## Further information

For contact information, see [www.u-blox.com/contact-u-blox](http://www.u-blox.com/contact-u-blox).

For more product details and ordering information, see the [product data sheet](#).

### Legal Notice:

u-blox or third parties may hold intellectual property rights in the products, names, logos and designs included in this document. Copying, reproduction, or modification of this document or any part thereof is only permitted with the express written permission of u-blox. Disclosure to third parties is permitted for clearly public documents only.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose, or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit [www.u-blox.com](http://www.u-blox.com).